## **OAK ALPINO**

Top layer aproxx. 3,6 mm



Maintenance oil white



## Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

## Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

## Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit www.admonter.eu/en/downloads/.

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! Repair and supplementary oils you can find in our Admonter price list. Further information about our products can be found at admonter.at

Grading	Grading Thickness Co		Width (mm)		Length (mm)	Texture	Finish		Profile
rustic	15	3-layer	192	classic	1850 / 2000 / 2400	brushed	ng		Tongue & groove

Backing: Solid wood / ng: natural oiled easy care / pc: natural oiled pro care / ml: matt lacquer

Technical information  More information (for example concerning fire classification) in the accompanying information to CE-marking at http://www.admonter.eu/en/downloads/												
Type of wood	Thickness (mm)	Weight [kg/m²]	Moisture content [%]	Lambda [W/m K]	D-Value R[m² K/W]	Hardness [N/mm²]	Fire classification					
Oak LH-RS	15	8,6	7+/-2	0,15	0,100	41	C <sub>f</sub> -s1					
Oak NH-RS	15	7,8	7+/-2	0,14	0,107	41	C <sub>ff</sub> -s1					

LH-RS: Hardwood-Backing / NH-RS: Softwood-Backing















