

# OAK STONE

Top layer approx. 3,6 mm

Maintenance oil white



## Admonter FLOORS on underfloor heating systems

Admonter FLOORS are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORS on underfloor heating systems!

## Admonter accessories

The wide range of accessories matches the Admonter FLOORS and includes flush-mount skirting and solutions for staircases.

## Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit [www.admonter.eu/en/downloads/](http://www.admonter.eu/en/downloads/).

**PLEASE NOTE:** natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! Repair and supplementary oils you can find in our Admonter price list. Further information about our products can be found at [admonter.at](http://admonter.at)



**FLOOR S**

Grading	Thickness (mm)	Construction	Width (mm)	Length (mm)	Texture	Finish	Profile			
noblesse	10	2-layer	120	small	1200	sanded / brushed	ng	Tongue & groove		
			158 / 180	classic	2000	sanded / brushed	ng	lock-it		
	15	3-layer	120	small	1200	sanded / brushed	ng	lock-it		
			158	classic	1850 / 2000 / 2400	sanded / brushed	ng ml	Tongue & groove		
			192	classic	1850 / 2000 / 2400	sanded / brushed	ng ml	lock-it		
			240	classic	2000 / 2400	sanded / brushed	ng ml	Tongue & groove		
elegance	10	2-layer	158	classic	2000	sanded / brushed	ng	lock-it		
	15	3-layer	158 / 192	classic	1850 / 2000 / 2400	sanded / brushed	ng ml	Tongue & groove / lock-it		
basic	10	2-layer	120	small	1200	sanded / brushed	ng	Tongue & groove		
			158 / 180	classic	2000	sanded / brushed	ng	lock-it		
	15	3-layer	120	small	1200	sanded / brushed	ng	lock-it		
			158	classic	1850 / 2000 / 2400	sanded / brushed	ng ml	Tongue & groove		
					alpin	ng	Tongue & groove			
					sanded / brushed	ng ml	lock-it			
					sanded / brushed	ng ml	Tongue & groove			
					cross / alpin	ng	Tongue & groove			
					sanded / brushed	ng ml	lock-it			
					240	classic	2000 / 2400	sanded / brushed	ng ml	Tongue & groove
naturelle	10	2-layer	158 / 180	classic	2000	sanded / brushed	ng	lock-it		
			158	classic	1850 / 2000 / 2400	sanded / brushed	ng ml	Tongue & groove		
	15	3-layer	192	classic	1850 / 2000 / 2400	sanded / brushed	ng ml	Tongue & groove		
					sanded / brushed	ng ml	lock-it			
			280	long	2800	sanded / brushed	ng	Tongue & groove		
					scraped	ng	Tongue & groove			
rustic	10	2-layer	120	small	1200	sanded / brushed	ng	Tongue & groove		
			158 / 180	classic	2000	sanded / brushed	ng	lock-it		
	15	3-layer	158	classic	1850 / 2000 / 2400	sanded / brushed	ng	Tongue & groove		
					sanded / brushed	ng	lock-it			
					sanded / brushed	ng	Tongue & groove			
					cross / alpin	ng	Tongue & groove			
					sanded / brushed	ng	lock-it			
					cross / alpin	ng	lock-it			
					240	classic	2000 / 2400	sanded / brushed	ng	Tongue & groove

Backing: Solid wood / ng: natural oiled easy care / pc: natural oiled pro care / ml: matt lacquer

## Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]	D-Value R[m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Oak	10	5,7	7+/-2	0,15	0,067	41	C <sub>s</sub> -s1
Oak small	13	7	7+/-2	0,14	0,094	41	C <sub>e</sub> -s1
Oak LH-RS	15	8,6	7+/-2	0,15	0,100	41	C <sub>e</sub> -s1
Oak NH-RS	15	7,8	7+/-2	0,14	0,107	41	C <sub>e</sub> -s1

LH-RS: Hardwood-Backing / NH-RS: Softwood-Backing



Admonter flooring is a 100 % natural product. A picture is never a substitute for the „real thing“. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.

# AUTENTICO

## OAK



Oak white rustic sanded



Oak stone rustic brushed

Oak also available as Oak Fumo.

Product	Grading	Thickn. (mm)	Con-struction	Width (mm)	Length (mm)	Texture	€/m <sup>2</sup>	Profile
Oak white	rustic	15	3-Layer	192	classic 2000	sanded pc	98,60	Tongue & groove
Oak stone	rustic	15	3-Layer	192	classic 2000	brushed pc	98,60	Tongue & groove

OAK AUTENTICO white/stone

Top layer approx. 3,6 mm  
Initial oil treatment required!  
Maintenance oil natural

